

## WIDE NECK DRUMS

### GENERAL INFORMATION

- Approved A-X.
- Airtight.
- Sealable with Compact Seal.
- Food grade approved.
- Maximum filling temperature 70°C.  
The contents must be cooled to 30°C before the drums are closed and stacked.
- Minimum use temperature -25°C.



### TECHNICAL SPECIFICATIONS

Reference	7002	7004	7005	7006	7010	7011	7015	7020	7026	7042	7055	7068
Capacity (L)	2,9	3,6	5	6	10	10	15	20	26	42	55	68
Diameter (mm)	198	198	198	198	274	274	274	274	316	410	410	410
Opening diam. (mm)	136	136	136	136	204	204	204	204	204	282	282	282
Height (mm)	158	173	222	263	239	239	328	418	426	416	518	632
Material	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE	HDPE
Drum color	White	White	White	White	White	White	White	White	White	White	White	White
Lid color	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
Antistatic version available	No	No	No	No	No	No	No	No	Yes	No	No	No
Available with handles	No	No	No	No	No	No	No	No	No	Yes	Yes	Yes
High print area (mm)	40	50	100	70	20	60	80	150	130	40	120	200
Field of the width of the label (mm)	230	230	230	300	300	300	300	300	330	330	330	330
Content Type	Solids and viscous materials											
Drum group	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III	I, II, III
Maximum weight (kg)	12	12	12	20	22	22	22	27	33	51	66	81
Pallets 1000x1200 mm	360	360	270	240	128	128	96	80	55	40	32	24